PRATT FLAMMABLE LIQUID STORAGE CABINET: **30L - 1 DOOR - 1 SHELF**

PRATT INDOOR FLAMMABLE LIQUID STORAGE CABINETS COMPLY WITH THE AUSTRALIAN STANDARD **AS 1940 "THE STORAGE & HANDLING OF FLAMMABLE** & COMBUSTIBLE LIQUIDS".

This cabinet is suitable for the storage of flammable or combustible liquids as classified by the United Nations criteria and the ADG Code for Dangerous Goods. For example: petrol, diesel, paints, solvents, thinners, kerosene, turpentine, white spirits, alcohol and ethanol etc. They are also suitable for the storage of aerosols where additional fire protection is required.

FEATURES & BENEFITS:

- Low profile under bench design.
- Constructed of double walled 1.2mm thick galvanised steel.
- Self closing door with speed adjustable hydraulic closure.
- 1 x 1.6mm thick, perforated, galvanised steel shelf.
- Continual stainless steel piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 45mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- 3 point self latching door mechanism.
- Recessed handle with keyed alike lock with 2 keys.
- External static earth connection and 1 x earthing wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection during transportation and storage.
- Flammable Liquid diamond and other decals applied.
- Optional additional shelves available.
- Includes set of 4 rubber feet.

-	WEIGHT:	53kg
		oong

- CAPACITY:
- DOORS:
- 1 1 (Inc. Base Level) - SHELVES:

30L

- EXTRA SHELF: 5517-29S

Ð	EXTERNAL (MM)		INTERNAL (MM)		
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
770	515	465	525	420	370

NOTE: 1. INTERNAL HEIGHT IS TAKEN FROM THE TOP OF THE SUMP SILL/BOTTOM SHELF TO THE CEILING. 2. FOR TOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT CLEARANCE LOCATIONS.







VOLUME CAPACITY	PER SHELF	TOTAL
2L Winchester	6	6
4L Winchester	4	4
4L Paint Can	4	4
20L Round Can	1	1

T: 1300 133 226 E: INFO@PRATTSAFETY.COM.AU AUSTRALIA NEW ZEALAND T: 0800 133 226 E: INFO@PRATTSAFETY.CO.NZ W: PRATTSAFETY.COM INTERNATIONAL E: INFO@PRATTSAFETY.COM