## PRODUCT INFORMATION



## FLAMMABLE LIQUID STORAGE CABINET - 60LTR, 1 DOOR, 2 SHELVES PRODUCT CODE: 5517AS

Pratt Indoor Flammable Liquid Storage Cabinets comply with the Australian Standard AS 1940-2017 "The Storage and Handling of Flammable and Combustible Liquids" in accordance with the cabinet specifications detailed in Clause 4.9.

This range of cabinets provide a fire resistant enclosure and help with good house-keeping practices. They are suitable for indoor storage of all flammable and combustible liquids as defined by the United Nations criteria and the Australian ADG Code for Dangerous Goods. For example: Petrol, Diesel, Paints, Solvents, Thinners, Kerosene, Turpentine, White Spirits, Alcohol and Ethanol etc. They are also suitable for the storage of Aerosols where additional fire protection is required.

## **FEATURES AND BENEFITS:**

- Constructed of double walled 1.2mm thick galvanised steel.
- Single self closing door with speed adjustable hydraulic closure.
- 2 x 1.6mm thick, perforated, galvanised steel shelves.
- Continual stainless steel piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 45mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- 3 point self latching door mechanism.
- Recessed handle with keyed alike lock with 2 keys.
- External static earth connection and 1 x earthing wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletized and packaged with strong cardboard for protection during transportation and storage.
- Flammable Liquid diamond and other decals applied.
- Optional additional shelves available.
- Includes set of 4 rubber feet.

Weight: 62kg Capacity: 60L Doors: 1

Shelves: 2 (Inc. Base Level)

Extra Shelf: 5517-29S





	EX.	EXTERNAL (mm)		INTERNAL (mm)		
	HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
Ī	1065	515	465	820	420	370

Note: 1. Internal height is taken from the top of the sump sill/bottom shelf to the ceiling.

2. For total external width measurement, add 6mm per vent bung for tight clearance locations.

VOLUME CAPACITY	PER SHELF	TOTAL
2L Winchester	6	12
4L Winchester	4	8
4L Paint Can	4	8
20L Round Can	1	2
Aerosol Can	30	60