

CLASS 4 DANGEROUS GOODS STORAGE CABINET - 160LTR, 2 DOORS, 2 SHELVES
PRODUCT CODE: 5530AC4

Pratt Indoor Class 4 Storage Cabinets comply with the new Standard AS/NZS 5026 “The Storage and Handling of Class 4 Dangerous Goods”.

This range of cabinets is for the storage of Class 4 chemicals in liquid or solid form as classified by the United Nations criteria and the ADG Code for Dangerous Goods. Please refer to the Standard. These include the following divisions: Flammable Solids, Spontaneously Combustible, and Dangerous When Wet.

FEATURES AND BENEFITS:

- Constructed of double walled 1.2mm thick galvanised steel.
- 2 x self closing doors with sequential mechanism.
- 2 x 1.6mm thick, perforated, galvanised steel shelves.
- Continual piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 45mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- Speed adjustable hydraulic door closures.
- Magnetic catches to hold doors in closed position to provide automatic release in the event of pressure build up.
- Recessed non lockable handle.
- External static earthing connection and 1 x bonding wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletized and packaged with strong cardboard carton for protection during transportation and storage.
- Either – Flammable Solid, Spontaneously Combustible or Dangerous When Wet diamonds and other decals applied.
- Optional additional shelves available.



Weight: 141kg
Capacity: 160L
Doors: 2
Shelves: 2 (Inc. Base Level)
Extra Shelf: 5545-29S



EXTERNAL (mm)			INTERNAL (mm)		
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
1295	1115	500	1015	1020	415

* AS/NZS 5026 specifies a maximum of 25kg or L for Category A, 50kg or L of Category B or 100kg or L of Category C, Class 4 Chemicals. Other capacity limitations do apply. Refer to the Standard for further details.

Note: 1. Internal height is taken from top of sump sill to the sequential chassis assembly.
2. For total external width measurement, add 6mm per vent bung for tight clearance locations.

VOLUME CAPACITY	PER SHELF	TOTAL
2L Winchester	6	12
4L Winchester	4	8
4L Paint Can	4	8
10L Paint Can	2	4
15L Paint Can	1	2
20L Paint Can	1	2
Aerosol Can	30	60