

CLASS 4 DANGEROUS GOODS STORAGE CABINET - 250LTR, 2 DOORS, 3 SHELVES
PRODUCT CODE: 5545AC4

Pratt Indoor Class 4 Storage Cabinets comply with the new Standard AS/NZS 5026 “The Storage and Handling of Class 4 Dangerous Goods”.

This range of cabinets is for the storage of Class 4 chemicals in liquid or solid form as classified by the United Nations criteria and the ADG Code for Dangerous Goods. Please refer to the Standard. These include the following divisions: Flammable Solids, Spontaneously Combustible, and Dangerous When Wet.

FEATURES AND BENEFITS:

- Constructed of double walled 1.2mm thick galvanised steel.
- 2 x self closing doors with sequential mechanism.
- 3 x 1.6mm thick, perforated, galvanised steel shelves.
- Continual piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 45mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- Speed adjustable hydraulic door closures.
- Magnetic catches to hold doors in closed position to provide automatic release in the event of pressure build up.
- Recessed non lockable handle.
- External static earthing connection and 1 x bonding wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletized and packaged with strong cardboard carton for protection during transportation and storage.
- Either – Flammable Solid, Spontaneously Combustible or Dangerous When Wet diamonds and other decals applied.
- Optional additional shelves available.



Weight: 185kg
Capacity: 250L
Doors: 2
Shelves: 3 (Inc. Base Level)
Extra Shelf: 5545-29S



| EXTERNAL (mm) | | | INTERNAL (mm) | | |
|---------------|-------|-------|---------------|-------|-------|
| HEIGHT | WIDTH | DEPTH | HEIGHT | WIDTH | DEPTH |
| 1825 | 1115 | 500 | 1545 | 1020 | 415 |

* AS/NZS 5026 specifies a maximum of 25kg or L for Category A, 50kg or L of Category B or 100kg or L of Category C, Class 4 Chemicals. Other capacity limitations do apply. Refer to the Standard for further details.

Note: 1. Internal height is taken from top of sump sill to the sequential chassis assembly.
2. For total external width measurement, add 6mm per vent bung for tight clearance locations.

| VOLUME CAPACITY | PER SHELF | TOTAL |
|-----------------|-----------|-------|
| 2L Winchester | 6 | 18 |
| 4L Winchester | 4 | 12 |
| 4L Paint Can | 4 | 12 |
| 10L Paint Can | 2 | 6 |
| 15L Paint Can | 1 | 3 |
| 20L Paint Can | 1 | 3 |
| Aerosol Can | 30 | 90 |