

PRATT ORGANIC PEROXIDE STORAGE CABINET: 60L - 1 DOOR - 2 SHELVES

PRATT INDOOR ORGANIC PEROXIDE STORAGE CABINETS COMPLY WITH THE AUSTRALIAN STANDARD AS2714 "THE STORAGE AND HANDLING OF ORGANIC PEROXIDES".

This range of cabinets is for the storage of Organic Peroxides in liquid or solid as classified by the United Nations criteria and the ADG Code for Dangerous Goods. These include chemicals such as: Acetyl Acetone Peroxide, Methyl Ethyl Ketone Peroxides, Dibenzoyl Peroxide etc.

FEATURES & BENEFITS:

- Constructed of double walled 1.2mm thick galvanised steel.
- Self closing door with speed adjustable hydraulic closure.
- 2 x 1.6mm thick, perforated, galvanised steel shelf.
- Continual piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 45mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- Magnetic catch to hold door in closed position to provide automatic release in the event of pressure build up.
- Recessed non lockable handle.
- External static earth connection and 1 x bonding wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection during transportation and storage.
- Organic Peroxide diamond and other decals applied.
- Optional additional shelves available.
- Includes set of rubber feet.

- **WEIGHT:** 62kg
- **CAPACITY:** 60L
- **DOORS:** 1
- **SHELVES:** 2 (Inc. Base Level)
- **EXTRA SHELF:** 5517-29S



EXTERNAL (MM)			INTERNAL (MM)		
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH
1065	515	465	820	420	370

NOTE:
 1. INTERNAL HEIGHT IS TAKEN FROM THE TOP OF THE SUMP SILL/BOTTOM SHELF TO THE CEILING.
 2. FOR TOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT CLEARANCE LOCATIONS.
 3. AS 2714 SPECIFIES A MAXIMUM OF 50KG OR L FOR TYPE B ORGANIC PEROXIDES.

VOLUME CAPACITY	PER SHELF	TOTAL
2L Winchester	6	12
4L Winchester	4	8
4L Round Can	4	8
20L Round Can	1	2